

Computer Vision I

Tim Luchterhand, Paul Nykiel (Group 17)

9. Juli 2018

1 Moravec Operator

```
1 I = double(imread('figures1.png'))/255.0;
2
3 M1 = [0 -1 0;
4         0 1 0;
5         0 0 0];
6 M2 = [0 0 -1;
7         0 1 0;
8         0 0 0];
9
10 M3 = [0 0 0;
11        0 1 -1;
12        0 0 0];
13
14 M4 = [0 0 0;
15        0 1 0;
16        0 0 -1];
17
18 D1 = imfilter(I, M1, 'replicate');
19 D2 = imfilter(I, M2, 'replicate');
20 D3 = imfilter(I, M3, 'replicate');
21 D4 = imfilter(I, M4, 'replicate');
22
23 D1 = D1 .* D1;
24 D2 = D2 .* D2;
25 D3 = D3 .* D3;
26 D4 = D4 .* D4;
27
28 B = ones(5,5) * 1/25;
29
```

```

30 A1 = imfilter(D1, B, 'replicate');
31 A2 = imfilter(D2, B, 'replicate');
32 A3 = imfilter(D3, B, 'replicate');
33 A4 = imfilter(D4, B, 'replicate');

34
35 S = A1 + A2 + A3 + A4;

36
37 A1 = A1 ./ S;
38 A2 = A2 ./ S;
39 A3 = A3 ./ S;
40 A4 = A4 ./ S;

41
42 threshold = 0.15;
43 M1 = (A1 + A2 - abs(A1 - A2))/2; % Stolen from: https://stackoverflow.com/questions/26634232/element-wise-matrix-min-in-matlab
44 M2 = (A3 + A4 - abs(A3 - A4))/2;
45 M = (M1 + M2 - abs(M1 - M2))/2;

46
47 underThreshold = find(M < threshold);
48 overThreshold = find(M >= threshold);
49 M(underThreshold) = 0;
50 M(overThreshold) = 1;

51
52 figure();

53
54 subplot(3,2,1);
55 imshow(A1);
56 title("0 degree Channel");
57 subplot(3,2,2);
58 imshow(A2);
59 title("45 degree Channel");
60 subplot(3,2,3);
61 imshow(A3);
62 title("90 degree Channel");
63 subplot(3,2,4);
64 imshow(A4);
65 title("135 degree Channel");
66 subplot(3,2,5);
67 imshow(M);
68 title("Detected Corners");
69 subplot(3,2,6);
70 imshow(I);
71 title("Original Image");


```

```


72
73 print("sh04ex01.eps", "-depsc");

```


0 degree Channel




45 degree Channel



90 degree Channel




135 degree Channel



Detected Corners



Original Image



Uncorrelated noise has a high frequency and is therefore strongly amplified by the derivation. As a result there are a lot more false positives in the image. To achieve better results one could use a low-pass-filter to suppress high frequencies (in this case the noise). This can be done by convolving the image with a gaussian kernel.

2 Structure Tensor

```

1 I = double(imread('figures1.png'))/255.0;
2
3 Sx = [-1 0 1;
4      -2 0 2;
5      -1 0 1];
6 Sy = [-1 -2 -1;
7      0 0 0;
8      1 2 1];
9

```

```

10 Ix = imfilter(I, Sx, 'replicate');
11 Iy = imfilter(I, Sy, 'replicate');
12
13 M = sqrt(Ix .* Ix + Iy .* Iy);
14
15 G = fspecial('gaussian', 13, 3);
16 S11 = imfilter(Ix .* Ix, G, 'conv');
17 S21 = imfilter(Iy .* Ix, G, 'conv');
18 S12 = imfilter(Ix .* Iy, G, 'conv');
19 S22 = imfilter(Iy .* Iy, G, 'conv');
20
21 x = zeros(size(Ix, 1) * size(Ix, 2), 1);
22 y = zeros(size(Ix, 1) * size(Ix, 2), 1);
23 u = zeros(size(Ix, 1) * size(Ix, 2), 1);
24 v = zeros(size(Ix, 1) * size(Ix, 2), 1);
25 eig1 = zeros(size(Ix, 1) * size(Ix, 2), 1);
26 eig2 = zeros(size(Ix, 1) * size(Ix, 2), 1);
27
28 H = zeros(size(I));
29 E = zeros(size(I));
30 C = zeros(size(I));
31
32 for yPos = 1:size(Ix, 1)
33     for xPos = 1:size(Ix, 2)
34         [V, D] = eig([S11(yPos, xPos) S12(yPos, xPos); S21(yPos, xPos)
35                     S22(yPos, xPos)]);
36         x((yPos-1)*size(Ix, 2) + xPos) = xPos;
37         y((yPos-1)*size(Ix, 2) + xPos) = yPos;
38
39         e1 = max(D(1, 1), D(2, 2));
40         e2 = min(D(1, 1), D(2, 2));
41
42         eig1((yPos-1)*size(Ix, 2) + xPos) = e1;
43         eig2((yPos-1)*size(Ix, 2) + xPos) = e2;
44
45         if e1 > 0.03
46             u((yPos-1)*size(Ix, 2) + xPos) = V(1, 1);
47             v((yPos-1)*size(Ix, 2) + xPos) = V(2, 1);
48         else
49             u((yPos-1)*size(Ix, 1) + xPos) = 0;
50             v((yPos-1)*size(Ix, 1) + xPos) = 0;
51     end
52
53     if e1 <= 0.03 && e2 <= 0.03

```

```

53             H( yPos , xPos ) = 1 ;
54         end
55
56     if e1 > 0.05 && e2 <= 0.03
57         E( yPos , xPos ) = 1 ;
58     end
59
60     if e1 > 0.05 && e2 > 0.05
61         C( yPos , xPos ) = 1 ;
62     end
63 end
64 end
65
66 figure( ) ;
67
68 subplot( 1 ,3 ,1 ) ;
69 imshow( M ) ;
70 title( " | \nabla I | " )
71
72 subplot( 1 ,3 ,2 ) ;
73 imshow( I ) ;
74 hold on ;
75 quiver( x ,y ,u ,v ) ;
76 title( " Quiver plot and the original image " ) ;
77
78 subplot( 1 ,3 ,3 ) ;
79 imshow( cat( 3 ,H,E,C ) ) ;
80 title( " Homogeneous in red , edges in green , corners in blue " ) ;
81
82 print( " sh04ex02 .eps " , "-depsc" );

```

